



- USB port for 3G/4G modem or extra storage
- 32 Simultaneous VPN Tunnels for remote offices or teleworkers
- SPI Firewall with Content Filtering
- Central Management for VigorAP & VigorSwitch
- SIM-base, 3G/4G LTE Router, CAT 6 up to 300Mbps connection speed (L model)

Connectivity

DSL Standard

- VDSL Profile: up to 35b
- Compliant with ITU-T VDSL2 G.993.2

Ethernet WAN

- IPv4
 - DHCP Client, Static IP, PPPoE, PPTP, L2TP
- IPv6
 - Tunnel Mode: TSPC, AICCU, 6rd, Static 6in4
 - Dual Stack: PPP, DHCPv6 Client, Static IPv6
- WAN Function
 - WAN Connection Fail-over
 - WAN Budgets
 - Load Balance/Route Policy
 - 802.1q Multi-VLAN Tagging

Ethernet LAN

- IPv4/IPv6 DHCP Server
- Static Routing/RIP
- Multiple Subnet
- Port/Tag-based VLAN

USB

- 3G/4G Modem as WAN
- Support Printer Server/File Sharing /Temperature Sensor

LTE Modem (L model)

- LTE (4G) at speeds of up to 300 Mbit/s
- SMS Sending/Receiving
- SMS Quota

VPN

- Up to 32 VPN Tunnels (including up to 16 SSL VPN Tunnels)
- Protocol: PPTP, IPsec, L2TP, L2TP over IPsec, IKEv2, SSL VPN, OpenVPN
- Encryption: MPPE and Hardware-based AES/DES/3DES
- Authentication: SHA-1
- IKE Authentication : Pre-shared Key and Digital Signature (X.509)
- LAN-to-LAN, Teleworker-to-LAN
- DHCP over IPsec
- IPsec NAT-traversal (NAT-T)
- Dead Peer Detection (DPD)
- VPN Pass-through
- VPN Wizard
- mOTP
- VPN Trunk: VPN Backup and Load Balance

Management

System Maintenance

- HTTP/HTTPS with 2-level Management (Admin/User)
- Logging via Syslog
- SNMP Management MIB-II (v2/v3)
- CLI (Command Line Interface, Telnet/SSH)
- Administration Access Control
- Web-based Diagnostic Functionality
- Firmware Upgrade via HTTP/TR-069/TFTP
- CWMP Support (TR-069)
- LAN Port Monitoring

Network Management

- Bandwidth/Session Management
- User Management by Time/Data Quota
- LAN DNS and DNS Proxy/Cache
- Dynamic DNS
- IGMP Snooping/Proxy v2 and v3
- QoS (DSCP/Class-based/4-level priority)
- Guarantee Bandwidth for VoIP
- Central AP Management
- Central VPN Management
- Central Switch Management

WLAN (ac model)

- Multiple SSID
- Security (Open, 64/128-bit WEP, WPA/WPA2, 802.1x)
- Hidden SSID
- Wireless Rate Control by SSID
- Wireless VLAN
- Wireless LAN Isolation
- MAC Address Access Control
- Access Point Discovery
- Wireless Client List
- WDS (Wireless Distribution System)
- WMM (Wi-Fi Multimedia)

Security

- Multi-NAT, DMZ Host, Port-redirection and Open Port
- Object-based Firewall
- MAC Address Filter
- SPI (Stateful Packet Inspection) (Flow Track)
- DoS/DDoS Prevention
- IP Address Anti-spoofing
- E-mail Alert and Logging via Syslog
- Bind IP to MAC Address
- Content Security (IM/P2P, URL, Keywords, Cookies,...)

VoIP (V model)

- Protocol: SIP, RTP/RTCP, ZRTP
- 12 SIP Registrars
- Dial Plan (Phone Book, Digit Map, Call Barring, Regional)
- Call Features (Call Waiting, Call Transfer, Scheduled DND, Hotline)
- Voice Codec (G.711 A/u law, G.726, G.729 A/B)
- Caller ID (FSK_ETSI, FSK_BELLCORE, DTMF)

Hardware Interface

- 1 x DSL WAN Port (WAN1)
- 6 x 10/100/1000Base-Tx LAN Switch, RJ-45 (P6 is shared by WAN2)
- 2 x Detachable Antennas (ac Model)
- 2 x Detachable LTE Antennas (L model)
- LTE SIM Card Slot (L model)
- 2 x USB Ports or 1 x USB Port (L model)
- 1 x Factory Reset Button
- 1 x Wireless On/Off/WPS Button (ac model)

	35b	G.Fast	WLAN	LTE	VoIP
Vigor2866	•	•			
Vigor2866ac/ax	•	•	•		
Vigor2866Lac/Lax	•	•	•	•	
Vigor2866Vac/Vax	•	•	•		•