



## **LCS-K702D/K704D**

### **2/4-Port DVI USB KVM Switch**

### **2/4 Cables included**

Longshines 2/4-port USB KVM with USB 2.0 HUB and Audio supports VGA monitor with the resolution up to 2048 x 1536@85Hz. LCS-K702/K704D features USB Keyboard and mouse support, one 2-port USB 2.0 HUB and Audio function. LCS-K702/K704D allows you to control computers by pushing button, hot key. With the powerful function, LCS-K702/K704D is the best KVM switch to satisfy your demand of Video connection.

#### **Features**

- ◆ Controls 2/4 computers from a single console (keyboard/mouse) over USB connection by using standard USB cables.
- ◆ Supports PS/2 keyboard/mouse and USB keyboard/mouse.
- ◆ Compliant with USB Specification Revision 2.0 and USB Device Class Definition for HID Revision 1.11.
- ◆ Four computers can share two USB downstream ports.
- ◆ Supports two types of switching:
  - a. Push button on front panel
  - b. Hot keys on PS/2 and USB keyboard
- ◆ LED display for easy status monitoring.
- ◆ Supply Microsoft Intellimouse 3 ~ 5 Key Mouse & Microsoft Natural Keyboard Pro series.
- ◆ Supports DVI-I interface.
- ◆ Supports DVI resolutions up to 1920 x 1200 @ 60HZ.
- ◆ Supports Windows 98/98SE/2000/Me/Xp/VISTA, Linux, MAC OS9/OSX, SUNMICRO Solaris 8 or later.
- ◆ Provides USB HUB switching in independent method or combination with the host switching (USB HUB Auto-Switch mode).
- ◆ Provides audio switching in independent method.
- ◆ Auto-Scan function (Time interval can be adjusted between 5-20 seconds when the Auto-Scan function is enabled).
- ◆ Plug and Play (Windows 98/SE users might need your Windows CD to install the HID driver for USB keyboard/mouse.)
- ◆ KVM firmware is upgradeable via on-board mini-USB download connector and external mini-programmer.





## Specification

<b>Model No.</b>	<b>LCS-K702D/K704D</b>	
Number Of Computer Controlled	2/4	
Selection Method	Push Button/Hot Key	
LEDs	HUB Switch LED ( Green)	
	PC Host LED (RED)	
	Auto Switch & Auto Scan LED (Green)	
Compliant with USB Version	USB1.0 / USB1.1/ USB2.0	
Compliant with HID Version	USB HID 1.11	
PC Connectors	Video	2/4 x HDB-15 male
	USB	2/4 x USB Type B female
	Microphone	2/4 x Audio Jack Female (Pink)
	Speaker	2/4 x Audio Jack Female (Green)
Console port	Video	1 x HDB-15 female
	Keyboard/Mouse	2 x USB Type A female
	Microphone	1 x Audio Jack Female (Pink)
	Speaker	1 x Audio Jack Female (Green)
USB Downstream ports	2 x USB Type A female	
Auto-Scan Interval	5,10,15,20 sec	
DDC, DDC2 monitor	Yes(Max.Resolution:1920x1200 @60Hz)	
Operating system supported	Win 98/98SE/ME/2000/XP/Vista/7	
	Mac OS9/X, Linux, Sun Micro OS	
Cables Included	2/4 sets of USB, VGA and audio cable	
Cable Length	1.8M	
Power	By External Adaptor	
Output Voltage	5V	
Output Current	2A	
Hot Pluggable	Yes	
Dimensions (LxWxH)	200 x 82 x 44 mm	
Unit Weight	900g	