



ICY BOX IB-PS102-PD

2-port USB fast charger for mobile devices

Key features

- Compact and energy efficient Power Delivery 3.0 charger
- Charges compatible devices with USB Power Delivery technology in the shortest possible time
- Power your mobile devices with up to 20 Watts via USB Type-C® Power Delivery
- Additional USB Type-A QC 3.0 port with up to 18 Watts
- Universal compatibility with many smartphones and tablets
- Intelligent chipset automatically recognizes the charging mode
- Safe use due to protection against overcharging, overvoltage, overheating and short circuit

Technical data

Model	IB-PS102-PD
Article no.	60887
EAN code	4250078172222
Brand	ICY BOX
Colour	Black
Material	Plastic
Input voltage	Input: 100-240 V, ~ 50/60 Hz, 0.5 A
Charge port	1x USB Type-C®, 1x USB Type-A
Total output	20 W
Charge port max. Output	See table
Charging standard	USB Power Delivery 3.0, Quick Charge 3.0
Main socket	EU plug CEE 7/16
Protection class	Protection class II, indoor
Efficiency Level	VI
Suitable environment	Indoor
Operating temperature	0° C – 40° C
Operating humidity	25% RH - 90% RH
Storage temperature	-25° C – 55° C
Storage humidity	10% RH - 90% RH
Plug & Play	Yes
System requirements	USB Type-C® Power Delivery or QC 3.0 enabled tablet or smartphone. Additional USB charging cables are not included.



Packing content

1x IB-PS102-PD, 1x Manual

Connection	Max. input: AC 100-240 V ~50/60 Hz 0.5 A
Type-C®	5 V@3 A = 15 W; 9 V@2.25 A = 20 W; 12 V@1.5 A = 18 W
Type-A	3.6 - 6.5 V@3 A = 19 W; 6.5 - 9 V@ 2 A = 18 W; 9 - 12 V@1.5 A = 18 W
Type-C® + Type-A	5 V @3.4 A (Max. 17 W)



ICY BOX **IB-PS102-PD** 2-port USB fast charger for mobile devices



Safe charging

The EU plug CEE 7/16 according to protection class II complies with the applicable requirements for indoor use and thus protects the connected end devices against overcharging, overvoltage, overheating and short circuit.



One for all

The handy plug-in power supply is extremely flexible. On the one hand, it is compatible with all common end devices and, on the other hand, simultaneous use of both USB ports is indispensable, which means synchronous charging via the USB Type-C® and Type-A interface.



Diversity on board

Regardless of whether your external device that needs to be charged has a USB Type-C® or a Type-A connector, this small quick charger accepts both connector types. The Type-C® connector has a Power Delivery 3.0 specification and the Type-A connector charges via the Quick Charge 3.0 protocol. So it's super practical in any case!

Logistical data

Packing unit: 56 pcs. / carton
Total weight: 5.700 kg
Gross weight: (with packing): 0.090 kg
Net weight: 0.052 kg

Dimension/carton: 470x220x300 mm
Dimension (with packing): 35x100x85 mm
Dimension of article: 30x42x80 mm
Country of origin: China