

# **MSDS** Report

<u> </u>	'X	<u> </u>	<u> </u>
Applicant's name	Shenzhen ErLang Shen Power Supply Technology Co., Ltd.		
Applicant's Address	608, Tangzhong joint Stock Company Building, Haibin New Village, Gushu Community, Xixiang Street, Bao'an District, Shenzhen		
Name of Sample	Li-ion Battery		
Model	ELS 602045		
Nominal Voltage	3.7V		
Rated Capacity	550mAh, 2.035Wh		
Weight	9.9g	(0)	
Size (L×W×T)	(47.0×19.7×5.5)mm		
Prepared By	Shenzhen TCT Testing Technology Co., Ltd. 2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China		
Report No.	TCT231219M121		

	Alisa Tu		Tomsin	
Written by: _	Mr Ma I'M	Approved by:	1000	
windon by		Approved by	,	

Inspected by: Effective Date: 2024. 01. 01



Report No. TCT231219M121 Hotline: 400-6611-140

E-mail: service@tct-lab.com

Page 1 of 8 http://www.tct-lab.com



Section 1- Chemic	cal Product & Company Identification
Name of Sample	Li-ion Battery
Manufacturer's name	Shenzhen ErLang Shen Power Supply Technology Co., Ltd.
Manufacturer's Address	608, Tangzhong joint Stock Company Building, Haibin New Village, Gushu Community, Xixiang Street, Bao'an District, Shenzhen
Tel	+86-13760349253
Emergency Tel	+86-13760349253
E-mail	xuqing20080606@163.com

Section 2- Hazard	Is Identification		
Classification of Danger	See section 14.		
		(	(3)
Primary Route(s) of Exposure	Eye, skin contact, ingestion.		
(c)	(c)	((())	
Health Hazard	The batteries are not hazardous manufacturer under normal cond fire, heat, leakage of internal comincluding but not limited to the fol circuited, put into fire, whacked worushed, and broken.	itions. In case of abus ponents, which could llowing cases: charge	se, there's Hazard of rupture, cause casualty loss. Abuses d for long time, short

E-mail: service@tct-lab.com

Report No. TCT231219M121 Hotline: 400-6611-140





Chemical Name	Concentration or concentration ranges (%)	CAS Number
Aluminum Foil	6.02	7429-90-5
Copper Foil	9.15	7440-50-8
Lithium Cobalt Oxide	40.87	12190-79-3
styrene-butadiene copolymer (SBR)	0.38	9003-55-8
Carbon (Proprietary)	18.83	7782-42-5
Sodium Carboxymethyl Cellulose(CMC)	0.32	9004-32-4
Polyethylene	5.00	9003-07-0
Ethyl methyl carbonate	4.27	623-53-0
		21324-40-3
Electrolyte (proprietary)	15.16	96-49-1
Liectionite (proprietary)	13.10	616-38-6
		623-53-0

Labeling according to EC directives.

No symbol and Hazard phrase are required.

Note: CAS number is Chemical Abstract Service Registry Number.

N/A=Not apply.

Section 4- First Aid Measures		
Eye	Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.	
Skin	Remove contaminated clothes and rinse skin with plenty of water or shower for 15 minutes. Get medical aid.	
Inhalation	Remove from exposure and move to fresh air immediately. Use oxygen if available.	
Ingestion	Ingesting damaged batteries, do not induce vomiting or give food or drink. Seek medical attention immediately.	

Report No. TCT231219M121 Hotline: 400-6611-140



Section 5- Fire F	ighting Measures
Characteristics of Hazard	Dusts at sufficient concentrations can form explosive mixtures with air. Combustion generates toxic fumes.
Hazardous Combustion Products	Carbon dioxide.
Fire-extinguishing Methods and Extinguishing Media	For small fires, use water spray, dry chemical, carbon dioxide or chemical foam.
Attention in Fire-extinguishing	Wear self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.
((0))	

Section 6- Accidental Release Measures		
Personal Precautions, protective equipment, and emergency procedures	In case of rupture. Attention! Corrosive material. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Refer to protective measures listed in Sections 7 and 8.	
Environmental Precautions	Prevent product from contaminating soil and from entering sewers or waterways.	
Methods and materials for Containment	Stop the leak if safe to do so. Contain the spilled liquid with dry sand or earth. Clean up spills immediately.	
Methods and materials for cleaning up	Absorb spilled material with an inert absorbent (dry sand or earth). Scoop contaminated absorbent into an acceptable waste container. Collect all contaminated absorbent and dispose of according to directions in Section 13. Scrub the area with detergent and water; collect all contaminated wash water for proper disposal.	

Section 7- Handling and Storage		
Handling	The battery may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity.	
Storage	Store in a cool, dry, well-ventilated area away from incompatible substances. Store locked up. Keep out of the reach of children.	

E-mail: service@tct-lab.com

Report No. TCT231219M121 Hotline: 400-6611-140 Page 4 of 8 http://www.tct-lab.com



Other Precautions	In case of rupture. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Use personal protection equipment.
-------------------	--

Section 8 - Exposure Controls/Personal Protection			
Engineering Controls	Use adequate ventilation to keep airborne concentrations low. If used under conditions that generate particulates, the ACGIH TLV-TWA of 3mg/m³ respirable fraction (10mg/m³ total) should be observed.		
	Eye and Face Protection: None required for consumer use. If there is a Hazard of contact: Tight sealing safety goggles. Face protection shield.		
Personal Protective Equipment	Skin and Body Protection: None required for consumer use. If there is a Hazard of contact: Wear protective gloves and protective clothing.		
	Respiratory Protection: No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.		

Section 9- Phy	sical and Chemical Properties	
	Appearance: Prismatic	
Physical State	Color: Silver	
	Odour: If leaking, smells of medical ether.	
Change in condi	tion	
рН	Not applicable as supplied.	
Flash Point	Not applicable unless individual components exposed.	
Flammability	Not applicable unless individual components exposed.	
Relative density:	Not applicable unless individual components exposed.	
Solubility (water)	Not applicable unless individual components exposed.	
Solubility (other)	Not applicable unless individual components exposed.	

E-mail: service@tct-lab.com

Report No. TCT231219M121 Hotline: 400-6611-140



Section 10 – Stability and Reactivity	
Chemical Stability	Stable under recommended storage conditions.
Possibility of Hazardous Reactions	None under normal processing.
Conditions to Avoid	Exposure to air or moisture over prolonged periods.
Incompatible materials	Acids, Oxidizing agents, Bases.
Hazardous Decomposition Products	Carbon oxides.

Section 11 – Toxicological Information	
Irritation	In the event of exposure to internal contents, vapour fumes may be very irritating to the eyes and skin.
Sensitization	Not Available.
Reproductive Toxicity	Not Available.
Toxicologically Synergistic Materials	Not Available.

Section 12-Ecological Information	
General note:	Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Anticipated behavior of a chemical product in environment/possible environmental impact/ ecotoxicity	Not Available.

Section 13 – Disposal Considerations	
Waste Treatment	Recycle or dispose of in accordance with government, state & local regulations.
Attention for Waste Treatment	Deserted batteries shouldn't be treated as ordinary trash. Shouldn't be thrown into fire or placed in high temperature. Shouldn't be dissected, pierced, crushed or treated similarly. Best disposal method is recycling.

## Section 14 – Transport Information

Report No. TCT231219M121 Hotline: 400-6611-140 Page 6 of 8
E-mail: service@tct-lab.com http://www.tct-lab.com



UN number	3480 & 3481
Proper shipping name	Lithium ion batteries (including lithium ion polymer batteries) or; Lithium ion batteries packed with equipment (including lithium ion polymer batteries) or;
	Lithium ion batteries contained in equipments (including lithium ion polymer batteries).
UN Classification (Transport hazard class):	Class 9 (PI965 Section IB) or N/A (PI966~967 Section II)
PG Packing Group:	N/A
Marine pollutant(Y/N):	N (S)
IMDG EmS No.:	F-A, S-I
	iser needs to be aware of, or needs to comply with, in conveyance either within or outside their premises.
ICAO / IATA:	Can be shipped by air in accordance with International Civil Aviation Organization (ICAO), TI or International Air Transport Association (IATA), DGR Packing Instruction 965 Section IB, 966~967 Section II appropriate of IATA DGR 65 <sup>th</sup> (2024 Edition) for transportation.
IMDG CODE:	The batteries are not restricted to IMDG Code 2022 Edition (Amdt 41-22) according to special provision 188.
DOT:	Other requirements for the US Department of Transportation (DOT) Subchapter C, Hazardous Materials Regulations if shipped in compliance with 49 CFR 173.185.
ADR/ ADN:	The batteries are not subject to the provisions of United Nations Economic Commission for Europe (UNECE) ADR/ADN if they meet the requirements of special provision 188 of Chapter 3.3. Applicable as from

In addition, to be permitted in transport each lithium cell and battery types must have passed the applicable tests set out in Subsection 38.3 of the UN Manual of Tests and Criteria.

### Section 15 – Regulatory Information

**Dangerous Goods Regulations** 

Recommendations on the Transport of Dangerous Goods-Model Regulations

Recommendations on the Transport of Dangerous Goods-Manual of Tests and Criteria

International Air Transport Association (IATA)

International Maritime Dangerous Goods

Technical Instructions for the Safe Transport of Dangerous Goods

Classification and code of dangerous goods

**OSHA Hazard Communication Standard** 

Toxic Substance Control Act (TSCA)

Code of Federal Regulations

In accordance with all Federal, State and local laws

Report No. TCT231219M121 Hotline: 400-6611-140 Page 7 of 8 http://www.tct-lab.com

E-mail: service@tct-lab.com






#### Section 16 - Additional Information

MSDS creation date: 2024 Version: 1.0


Sample photo:





To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

The data/information contained herein has been reviewed and approved for general release on the basis that this document contains no export controlled information.





Report No. TCT231219M121

Hotline: 400-6611-140