

9-1 USB-C® Dual HDMI™ 100W Hub



Product Name:
9-1 USB-C® Dual HDMI™ 100W Hub

Product Series: Hub

Product Code: CSV-2552

EAN code: 8719214473556

UPC code: 841615103805

Description:

- Dual Displays hub with DP1.4 Alt mode, OUTPUT: 2x HDMI™ Connect up to 2 displays with a single USB-C® input, supporting resolutions up to two times 4K60Hz screen for an immersive multi-monitor setup.
- 1 GBASE-T GIGABIT ETHERNET: Features a 1Gbps network controller that delivers speeds of 10/100/1000 Mbps; For laptops / devices without an Ethernet, such as MacBook / iPad Air / Pro; USB-C® connectivity while providing power for PD3.0 charging.
- 1 PORT USB Type-C®: Expand the connectivity of a USB-C® computer by adding 4 USB Ports 2x USB Type-A, 1x Type-C® and a Power Delivery 3.0 USB-C® Port Max. 100Watt upstream.
- 2 dedicated Card reader slots Micro SD/SD supports SD3.0(UHS-II) with max 104Mbps, card slots work simultaneously.

Features:

- Support DP1.4 Alt mode.
- One HDMI™ (close to Micro SD/SD) supports max 8K30Hz, another one supports max 4K60Hz.
- Support dual 4K60Hz under MST mode (Windows System). Your PC has to support DP1.4 and DSC.
- Support dual 4K60Hz (SST on MacOS).
- Two USB-A ports and one USB-C® data port. The USB-C® and one USB-A port support speeds up to 5 Gbps, while the other USB-A port is USB 2.0.
- Support Secure Digital v3.0 UHS-I (Ultra High Speed): SDR12 (12.5Mbyte/s)/SDR25(25Mbyte/s)/SDR50(50Mbyte/s)/DDR50(50Mbyte/s)/SDR104(104Mbyte/s).
- Allow 2 card slots to work simultaneously.
- Support 10/100/1000Mbps.
- USB Type-C® PD Charging port supports PD3.0 with max 100 Watt.
- Support Fast Role Swap of PD 3.0, the connected device will not get disconnected while plugging out PD Adapter.

Supported resolutions:
8K30Hz, 4K60Hz or 2x 4K60Hz

OS Support:
Windows 11, MacOS 15




In the box:
• 1x 9-1 USB-C® Dual HDMI™ 100W Hub

Available Interfaces
Input:
• 1x USB-C®

Output:
• 1x USB-C® PD
• 2x HDMI™
• 1x MicroSD/SD
• 1x USB-C®
• 2x USB-A
• 1x Ethernet

Other info:
• Box size: 14.5 x 14.5 x 4.5cm / 5.71 x 5.71 x 1.77in
• Device size: 11.5 x 5.9 x 1.4cm / 4.53 x 2.32 x 0.55in
• Cable length approx.: 17cm / 6.7in
• Connector dimensions:
USB-C® 3.62 x 1.2 x 0.63cm / 1.43 x 0.47 x 0.25in
• Device Weight: 121g / 4.27oz
• Box Weight: 45g / 1.59oz
• LDPE Bag Weight: 3g / 0.11oz
• Total Weight: 169g / 5.96oz
• Meets ROHS, FCC, and CE EMI requirements



Please use one of our Extension/Adapter cables to connect to your devices: In case you need assistance to choose the correct cable, please visit our website www.club-3d.com or feel free to mail us at support@club-3d.com and it will be our pleasure to assist you.

Club 3D uses Bio-Degradable bags according to the EN/DIN 13432.



Club 3D uses environmentally friendly packaging and is printed on recycled paper.



Disclaimer: While we endeavour to provide the most accurate, up-to-date information available, the content on this document may be out of date or include omissions, inaccuracies or other errors. Products might obtain a certification during their lifetime. This doesn't change or alter the product specifications and/or performance in any way. Club 3D will provide the updated information on their website www.club-3d.com at her discretion. Therefore Club 3D does not accept any rights claimed on the content of this document. Please refer to a full overview of our Legacy Terms and Conditions on www.club-3d.com. All other brand names are trademarks or registered trademarks and are the property of their respective owners. All content is subject to change without prior notice.